



Compliance Certificate

4 – ZERO Flexible Nude Core

Vic Air Supplies 4 – Zero flexible Nude Core has been tested and meets all requirements of Australian Standards 4252 and Building Codes of Australia for Domestic and Commercial Air Handling Systems.

PRODUCT: Aluminium/Polyester laminate Flexible Nude Core (4-Zero).

CONSTRUCTION: Aluminum/Polyester inner surface, Metalised Polyester outer surface multi-layered construction containing high level flame retardant Water based adhesive with high tensile wire helix encapsulated.

LENGTH: 6 Metre lengths.

DIAMETERS: 4", 5", 6", 8" 10", 12", 14", 16", 18", 20",22" INCH.

OPTIONS: Standard Plain or Acoustic.

OPERATING PRESSURE RANGE: 1000 Pa positive, 200 Pa negative

OPERATING TEMPERATURE RANGE: -10C TO +80C

TEST STANDARD	DESCRIPTION	RESULT
AS/NZS 1530.3 - 1999	Ignitability Index	0
AS/NZS 1530.3 - 1999	Spread of Flame Index	0
AS/NZS 1530.3 - 1999	Heat Evolved Index	0
AS/NZS 1530.3 - 1999	Smoke Developed Index	0
UL181	Burning	Pass
UL181	Mould Growth & Humidity	Pass
UL181	Temperature	Pass
UL181	Puncture	Pass
UL181	Static Load	Pass
UL181	Impact	Pass
UL181	Pressure	Pass
UL181	Collapse	Pass
UL181	Tension	Pass

